

Balcony Coat

An incredibly tough and flexible waterproof coating



“maintenance made easy”



PRODUCT DESCRIPTION

Balcony Coat has been formulated to easily withstand pedestrian use tables and chairs. Balcony Coat retains high elasticity to cope with expansion and contraction well known on external areas and is an easy to use single pack, UV resistant non yellowing formulation. Balcony Coat is totally waterproof.

TYPICAL USES

Balcony Coat can be used as a transparent flexible sealer coat and is ideal for both concrete and tiled areas. Please note that it cannot be used in swimming pools, but is perfectly suitable for use in the surrounding areas.

SUITABLE SUBSTRATES

Concrete, terrazzo, quarry tiles, clay or ceramic tiles, mosaics, etc.

COLOUR

Balcony Coat is translucent in colour

PACKAGING

Balcony Coat is distributed in 5 Ltr tins



DIRECTIONS FOR USE

SURFACE PREPARATION

Before application of Balcony Coat, a suitable primer should be applied, this includes BC Primer. If application surface is glazed tiles, they must be clean and dry and BC Primer should be used. Surfaces for primers should be free of all oil, grease and cement dust.

APPLICATION

Apply BC Primer using a cloth at a rate of 20-25m² per 0.8kg unit. After a drying time of approximately 30 minutes the primed surface can be coated. Balcony Coat is ready for use after opening the tin. It is most suitably applied using a toothed trowel or squeegee with number 10 teeth. It is important that no area is coated with less than 0.4 or more than 0.7kg per m².

POT LIFE

PLEASE NOTE

Once units are opened, they should be used by the next day.

CURING TIMES

After application, a drying time minimum of 12 hours should be allowed before the second coat can be applied. Drying time depends on temperature and humidity. Please note: the first coat should be fully cured prior to application of further coats as necessary.

APPLICATION TEMPERATURE

We recommend that Balcony Coat be applied in a temperature range between 10 - 25°C.

COVERAGE

A 0.8kg unit of BC Primer will cover 20-25m² per coat. A 5.0kg unit of Balcony Coat will cover 10-25m² per coat.

SHELF LIFE AND STORAGE

Balcony coat can be stored for a maximum of 6 months in a room between 15-25°C, out of direct sunlight in unopened.

HEALTH & SAFETY

Before using this product, please ensure you have received & read carefully both the Hazard Label applied to the container & the relevant Material Safety Data Sheets.

ANY QUESTIONS?

Please do not hesitate to contact us for advice regarding the use of this product or its suitability for your particular application. Our aim is to provide all the technical help you need to make an informed choice & achieve total success.

Polycote Technical Helpline

01234 846400

All reasonable care has been taken in supplying the above information. However, any figures quoted do not constitute a specification but represent typical values obtained. It is the customer's responsibility to ensure for himself that the product is fit for the intended purpose & that conditions are suitable. Any technical advice is offered in good faith, but without warranty. This is also applicable when proprietary rights & third parties are involved. In the light of the Company's policy of continual research & development, it is the customer's responsibility to ensure that the information contained herein has not been superseded.

REV: 01/09