

# Stoneguard™



“maintenance made easy”

**Invisible penetrating masonry waterproofer**



## PRODUCT DESCRIPTION

**Stoneguard™ is a unique single pack water-dispersed fluoropolymer based coating providing a protective barrier against water, oil, atmospheric pollutants and other contaminants when applied to stone, concrete and other porous mineral surfaces. Its very low viscosity formulation penetrates and seals the substrate with a durable chemical bond, yet is totally invisible, having no effect on the appearance or characteristics of the treated surface. It does not prevent the escape of water vapour and therefore retains the breatheability of construction materials.**

## TYPICAL USES

Stoneguard™ is a very versatile product suitable for exterior and interior use on walls, floors, and paved areas. Typical applications include water-repellent treatment of brick and stone buildings - it is ideal for listed buildings - and to give oil resistance to driveways, parking bays and paved areas, factory walls, aircraft hangars and other surfaces vulnerable to oil and liquid penetration.

## SUITABLE SUBSTRATES

Stoneguard™ may be applied to brick, block, stone, marble, terracotta, plaster, plasterboard, concrete, mortar, grout and many other porous surfaces.

## COLOUR & PACKAGING

Stoneguard™ is a clear colourless liquid and is supplied in 5.0 litre units.



Image depicts a typical stone wall damaged by contaminants.

**DIRECTIONS FOR USE Cont.****SURFACE PREPARATION**

Remove all loose, friable or flaking material and any fungal or algae growth. Ensure the surface is clean, dry and free of oil or other contamination.

**APPLICATION**

A single thorough coat is normally sufficient. Depending on the size and evenness of the surface to be treated, Stoneguard may be applied by brush, roller if the area is very flat, mop or low pressure garden sprayer. Fine spray should not be used and precautions must be taken to prevent inhalation of airborne droplets. Any pooling should be brushed out.

***Tile grout sealing -***

apply Stoneguard over entire tiled area with a brush or roller, re-coating after 1 hour. Avoid contact with water for 24 hours, then remove residue from glazed tile surfaces with soap and water.

**CURING TIME**

Depending on temperature, Stoneguard™ is touch dry within 30 minutes and will withstand traffic and rain within 3 hours. Avoid water spillage for 12 hours. Full chemical curing is achieved within 24 hours.

**APPLICATION TEMPERATURE**

Application temperature should be above +8°C

**COVERAGE**

The coverage per 5L unit of Stoneguard™ is approximately 50m<sup>2</sup>, depending on the texture and porosity of the substrate.

**CLEANING**

Brushes, rollers and spray should be immersed in water when not in use. When application is complete, wash equipment with water.

**SHELF LIFE & STORAGE**

Shelf life is 12 months subject to conditions of storage. Store at a temperature between +5°C and +30°C. Protect from frost.

**HEALTH & SAFETY**

**Before using this product, please ensure you have received & read carefully both the Hazard Label applied to the container & the relevant Material Safety Data Sheets.**

**ANY QUESTIONS?**

Please do not hesitate to contact us for advice regarding the use of this product or its suitability for your particular application. Our aim is to provide all the technical help you need to make an informed choice & achieve total success.

Polycote Technical Helpline

**01234 846400**

All reasonable care has been taken in supplying the above information. However, any figures quoted do not constitute a specification but represent typical values obtained. It is the customer's responsibility to ensure for himself that the product is fit for the intended purpose & that conditions are suitable. Any technical advice is offered in good faith, but without warranty. This is also applicable when proprietary rights & third parties are involved. In the light of the Company's policy of continual research & development, it is the customer's responsibility to ensure that the information contained herein has not been superseded.

REV: 02/09